

PRODUCT DATA

Technical description

| | |
|---------------------|--|
| Surface | Three-dimensional interlaced melamine resin |
| Overlay | Melamine resin impregnated paper with corundum |
| Deco`r | Melamine resin impregnated printed paper |
| Core layer | HDF High Density Fiberboard |
| Balance film | Melamine resin impregnated paper |

Installation

Mechanical locking system , Clic-System – much easier to install ,up to 50% quicker to install (against other clic systems). Floating Installation according to the installation description

Slip resistance Technical class DS

Thermal conductivity Thermal resistance according to DIN EN 12667
Thickness 8 mm $R = 0,0587 [(m^2 * K)/W]$

TECHNICAL SHEET

| Test items Standard | Value Lodgi | actual testing result |
|--------------------------|--------------------|-----------------------|
| Abrasion(AC3) | ≥ 2000 rounds | |
| Density (KG/M3) | ≥ 850 | 900 |
| Moisture Content (%) | 3.0~10.0 | 4.7 |
| Modulus of rupture (Mpa) | ≥ 35 | 38.1 |
| Inter Bonding (Mpa) | ≥ 1.0 | 1.33 |
| Inter Bonding (Mpa) | ≥ 1.0 | 1.12 |
| Thickness swelling (%) | ≤ 18 | 11.5 |
| Formaldehyde emission | E1 ≤ 1.5 mg/L | 1 |

Product Code Range 101 >> 117